Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

Reviewed on 11/15/2018

# **1** Identification

- · Product identifier
- · Product Name: <u>1000 µg/mL Arsenic</u>
- · Part Number:
- PLAS2-2M
- PLAS2-2Y PLAS2-2T
- PLAS2-2X
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: SPEX CertiPrep, LLC.
  203 Norcross Ave, Metuchen, NJ 08840 USA
- · Information department: product safety department
- Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

#### 2 Hazard(s) identification

· Classification of the substance or mixture

GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling:
- arsenic
- Hazard statements H315 Causes skin irritation.
- 11313 Causes skin tritation.
- H319 Causes serious eye irritation. H350 May cause cancer.
- · Precautionary statements
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Read label before use.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- If skin irritation occurs: Get medical advice/attention.
- Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

Reviewed on 11/15/2018

Product Name: 1000 μg/mL Arsenic	
· Classification system: · NFPA ratings (scale 0 - 4)	(Contd. of page 1)
$\begin{array}{c} 2 \\ 0 \\ 0 \\ 0 \\ \mathbf{R} \\ \mathbf{R} \\ \mathbf{R} \\ 0 \\ $	
· HMIS-ratings (scale 0 - 4)	
HEALTH*2FIRE0REACTIVITY $Reactivity = 0$	
· Other hazards	
• Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
7697-37-2 nitric acid	2.0%	
7440-38-2 arsenic	0.1%	
· Chemical identification of the substance/preparation		
7732-18-5 water, distilled, conductivity or of similar purity	97.9%	

## 4 First-aid measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- $\cdot \textit{Most important symptoms and effects, both acute and delayed} \textit{ No further relevant information available.}$
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# · Protective Action Criteria for Chemicals

·	PA	C-1
---	----	-----

7697-37-2 nitric acid	0.16 ppm
7440-38-2 arsenic	$1.5 mg/m^3$
	(Contd. on page 3)

Printing date 11/15/2018

## Product Name: 1000 µg/mL Arsenic

	(Contd. of page 2)
· PAC-2:	
7697-37-2 nitric acid	24 ppm
7440-38-2 arsenic	17 mg/m <sup>3</sup>
· PAC-3:	
7697-37-2 nitric acid	92 ppm
7440-38-2 arsenic	100 mg/m <sup>3</sup>

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:	
7697	-37-2 nitric acid	
PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm	
REL	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm	
TLV	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5.2 mg/m <sup>3</sup> , 2 ppm	
7440	-38-2 arsenic	
PEL	Long-term value: 0.5* 0.01** mg/m <sup>3</sup> as As; *organic**inorg. compds.; 29 CFR 1910.1018	
REL	Ceiling limit value: 0.002 mg/m <sup>3</sup> as As; 15min; See Pocket Guide App. A	
TLV	Long-term value: 0.01 mg/m <sup>3</sup> as As; BEI	
· Ingr	edients with biological limit values:	
7440	-38-2 arsenic	
BEI	35 µg As/L	
	Medium: urine	
	Time: end of workweek	
	Parameter: Inorganic arsenic plus methylated metabolites (background)	
· Addi	tional information: The lists that were valid during the creation were used as basis.	
	osure controls	
	onal protective equipment:	
	eral protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.		
Wash hands before breaks and at the end of work.		
	d contact with the eyes and skin.	
	iratory protection:	
In ca	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is pondent of circulating air.	
	(Contd. on page 4)	

US

Reviewed on 11/15/2018

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

#### Product Name: 1000 µg/mL Arsenic

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties		
· General Information		
· Appearance:		
Form:	Liquid	
Color:	According to product specification	
· Odor:	Characteristic	
· Odour Threshold:	Not applicable.	
· pH-value:	Not applicable.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
<b>Boiling point/Boiling range:</b>	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not applicable.	
• Auto igniting:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not applicable.	
Upper:	Not applicable.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F)	1.01479 g/cm³ (8.46842 lbs/gal)	
· Relative density	Not applicable.	
· Vapor density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	e <b>r):</b> Not applicable.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Water:	97.9 %	
VOC content:	0.00 %	
Solids content:	0.1 %	
	(Contd. on page 5)	

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

#### Product Name: 1000 µg/mL Arsenic

· Other information

No further relevant information available.

**10 Stability and reactivity** 

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer) 7440-38-2 arsenic 1 · NTP (National Toxicology Program) 7440-38-2 arsenic Κ · OSHA-Ca (Occupational Safety & Health Administration) 7440-38-2 arsenic

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN3264

(Contd. on page 6)

# Reviewed on 11/15/2018

(Contd. of page 4)

Page 6/8

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

Reviewed on 11/15/2018

	(Contd. of pag
UN proper shipping name DOT ADR IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC AC SOLUTION)
Transport hazard class(es)	SOLUTION)
DOT	
Class	8 Corrosive substances
Label	8
ADR, IMDG, IATA	
Class Label	8 Corrosive substances 8
Packing group DOT, ADR, IMDG, IATA	111
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Corrosive substances 80 F-A,S-B
Segregation groups	Acids
Stowage Category Stowage Code	A SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARP(	· · · ·
Code	Not applicable.
Transport/Additional information:	
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
Excepted quantumes (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITI ACID SOLUTION), 8, III

# **15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
 Section 313 (Specific toxic chemical listings):

 7697-37-2
 nitric acid
 7440-38-2
 arsenic

 FSCA (Toxic Substances Control Act):

 All ingredients are listed.
 Proposition 65
 Chemicals known to cause cancer:

 7440-38-2
 arsenic

Printing date 11/15/2018

Reviewed on 11/15/2018

#### Product Name: 1000 µg/mL Arsenic

	(Contd. of page 6)
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
7440-38-2 arsenic	A
· TLV (Threshold Limit Value established by ACGIH)	
7440-38-2 arsenic	AI
·NIOSH-Ca (National Institute for Occupational Safety and Health)	

7440-38-2 arsenic

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



GHS07 GHS08

· Signal word Danger

- · Hazard-determining components of labeling:
- arsenic · Hazard statements
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H350 May cause cancer.
- · Precautionary statements
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Read label before use.

Wear protective gloves/protective clothing/eye protection/face protection.

- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:
- SPEX CertiPrep, LLC. 1-732-549-7144
- · Date of preparation / last revision 11/15/2018 / -
- · Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit

US

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018

Product Name: 1000 µg/mL Arsenic

BEI: Biological Exposure Limit Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Carc. IA: Carcinogenicity – Category IA Reviewed on 11/15/2018

(Contd. of page 7)

US